



PETROL

**KATALOG IZDELKOV**  
**PRODUCTS CATALOGUE**

## MOTORNA OLJA ENGINE OILS

### Sintetična motorna olja Synthetic Engine Oils

#### PETROL 505.01 5W-40

SAE 5W-40, VW 505.01, 500.00, 505.00, Ford WSS-M2C917-A

**PETROL 505.01 5W-40** je specialno večgradacijsko popolnoma sintetično motorno olje namenjeno predvsem za dieselske motorje s sistemom enotne tlačilke in šobe za vbrizgavanje goriva, ki zahtevajo uporabo olja odobrenega pod specifikacijo VW 505.01. Njegova uporaba se priporoča tudi za vse motorje, kjer se zahteva ustreznost specifikacijama VW 500.00 in 505.00.

*PETROL 505.01 5W-40 is a fully synthetic multigrade motor oil primarily intended for use in passenger diesel engines with unit injectors, requiring VW 505.01 approved engine oils. It is also recommended for use where oils that comply with specifications VW 500.00 and 505.00 are required.*

#### Tipične lastnosti / Characteristics:

Viskoznost / Kinematic viscosity (100°C; mm <sup>2</sup> /s):	14,3
Plamenišče / Flash point (°C):	218
Točka tečenja / Pour point (°C):	- 42
Gostota / Density (kg/l):	0,857

#### Polnjenje:

plastenki 1 l in 4 l, soda 60 l in 205 l

#### Filling:

plastic bottles 1 l & 4l, barrels 60 l & 205 l

#### PETROL Energy 5W-30

SAE 5W-30, ACEA A1-04, B1-04, API SL/EC, ILSAC GF-3, Ford/Jaguar WSS M2C 913-B ...

**PETROL Energy 5W-30** je vrhunsko, lahko tekoče fuel economy motorno olje, namenjeno novejšim osebnim vozilom. Nižja viskoznostna gradacija in edinstvena tehnologija omogočata tudi do 6 % prihranka na gorivu.

*PETROL Energy 5W-30 is a top quality, low viscosity fuel economy motor oil designed for modern passenger vehicles. Lower viscosity grade and unique technology provide up to 6 % fuel saving.*

#### Tipične lastnosti / Characteristics:

Viskoznost / Kinematic viscosity (100°C; mm <sup>2</sup> /s):	9,95
Plamenišče / Flash point (°C):	220
Točka tečenja / Pour point (°C):	- 45
Gostota / Density (kg/l):	0,850

#### Polnjenje:

plastenki 1 l in 4 l, soda 60 l in 205 l, kontejner

#### Filling:

plastic bottles 1 l & 4l, barrels 60 l & 205 l, container



## PETROL Top Sint 5W-40

SAE 5W-40, ACEA A3-04, B3-04, B4-04, API SL/CF, VW 502.00/505.00, MB 229.3, BMW Longlife Oil 98, Porsche, Opel/GM-LL-B-025 ...

**PETROL Top Sint 5W-40** je popolnoma sintetično, lahko tekoče motorno olje za vse izjemno zmogljive motorje osebnih vozil. Sintetična tehnologija omogoča lažji zagon hladnega motorja, manjšo porabo goriva ter podaljšane intervale menjave.

***PETROL Top Sint 5W-40** is fully synthetic, low viscosity motor oil recommended for all heavy-duty passenger car engines. Synthetic technology provides easy starting of the cold engine and lower fuel consumption; it eliminates the need for frequent oil changes.*

### Tipične lastnosti / Characteristics:

Viskoznost / Kinematic viscosity (100°C; mm <sup>2</sup> /s):	14,4
Plamenišče / Flash point (°C):	226
Točka tečenja / Pour point (°C):	- 42
Gostota / Density (kg/l):	0,856

### Polnjenje:

plastenki 1 l in 4 l, soda 60 l in 205 l, kontejner

### Filling:

plastic bottles 1 l & 4 l, barrels 60 l & 205 l, container

## Delno sintetična motorna olja

### Part-Synthetic Engine Oils

## PETROL Garant 10W-40

SAE 10W-40, ACEA A3-04, B3-04, B4-04, API SL/CF, 505.00, MB 229.1, ...

**PETROL Garant 10W-40** je delno sintetično motorno olje za najzahtevnejša osebna in manjša dostavna vozila. Omogoča lažji zagon hladnega motorja, manjšo porabo goriva ter zagotavlja vrhunsko zaščito motorjev v vseh pogojih obratovanja.

***PETROL Garant 10W-40** is a partly synthetic motor oil recommended for heavy-duty passenger cars and delivery vans. It provides easy starting of the cold engine, lower fuel consumption and excellent protection of engines in all operating conditions.*

### Tipične lastnosti / Characteristics:

Viskoznost / Kinematic viscosity (100°C; mm <sup>2</sup> /s):	14,6
Plamenišče / Flash point (°C):	226
Točka tečenja / Pour point (°C):	- 27
Gostota / Density (kg/l):	0,878

### Polnjenje:

plastenki 1 l in 4 l, soda 60 l in 205 l, kontejner

### Filling:

plastic bottles 1 l & 4 l, barrels 60 l & 205 l, container



## PETROL Garant Diesel 10W-40

SAE 10W-40, ACEA B3-04, B4-04, API CF, VW 505.00, MB 229.1,...

**PETROL Garant Diesel 10W-40** je specialno delno sintetično motorno olje, primerno za vse vrste osebnih dieselskih vozil. Omogoča lažji zagon hladnega motorja, manjšo porabo goriva ter zagotavlja vrhunsko zaščito dieselskih motorjev v vseh pogojih obratovanja.

*PETROL Garant Diesel 10W-40 is a special, partly synthetic motor oil, suitable for all types of Diesel passenger cars. It provides easy starting of the cold engine, lower fuel consumption and excellent protection of diesel engines in all operating conditions.*

### Tipične lastnosti / Characteristics:

Viskoznost / Kinematic viscosity (100°C; mm <sup>2</sup> /s):	14,5
Plamenišče / Flash point (°C):	226
Točka tečenja / Pour point (°C):	- 30
Gostota / Density (kg/l):	0,878

### Polnjenje:

plastenki 1 l in 4 l, soda 60 l in 205 l, kontejner

### Filling:

plastic bottles 1 l & 4 l, barrels 60 l & 205 l, container

## Mineralna motorna olja

### Mineral Engine Oils

## PETROL Avant 15W-40

SAE 15W-40, ACEA A2-96/3, B2-98/2, API SL/CF, VW 501.01/505.00, MB 229.1 ...

**PETROL Avant 15W-40** je univerzalno motorno olje, primerno za vse vrste osebnih in manjših dostavnih vozil. Zagotavlja odlično zaščito pred obrabo in korozijo ter preprečuje nastajanje usedlin v motorju.

*PETROL Avant 15W-40 is an universal motor oil, suitable for all types of passenger cars and delivery vans. It provides outstanding performance with respect to anti-wear and corrosion resistance, and prevents formation of engine deposits.*

### Tipične lastnosti / Characteristics:

Viskoznost / Kinematic viscosity (100°C; mm <sup>2</sup> /s):	14,5
Plamenišče / Flash point (°C):	228
Točka tečenja / Pour point (°C):	- 30
Gostota / Density (kg/l):	0,883

### Polnjenje:

plastenki 1 l in 4 l, soda 60 l in 205 l, kontejner

### Filling:

plastic bottles 1 l & 4 l, barrels 60 l & 205 l, container



## PETROL Avant 20W-50

SAE 20W-50, ACEA A2-96/3, B2-98/2, API SL/CF, VW 501.01/505.00, MB 229.1 ...

**PETROL Avant 20W-50** je univerzalno motorno olje višje viskoznosti, primerno za vse vrste osebnih in manjših dostavnih vozil. Zaradi višje viskoznosti je še posebej primerno za starejša vozila, kjer se pojavljajo težave s porabo in tlakom olja. Zagotavlja odlično zaščito pred obrabo in korozijo ter preprečuje nastajanje usedlin v motorju.

*PETROL Avant 20W-50 is an universal motor oil, suitable for all types of passenger cars and delivery vans. Due to its high viscosity, it is particularly recommended for older vehicles with oil consumption and pressure difficulties. It provides outstanding performance with respect with antiwear and corrosion resistance, and prevents formation of engine deposits.*

### Tipične lastnosti / Characteristics:

Viskoznost / Kinematic viscosity (100°C; mm <sup>2</sup> /s):	18,0
Plamenišče / Flash point (°C):	234
Točka tečenja / Pour point (°C):	- 27
Gostota / Density (kg/l):	0,889

### Polnjenje:

plastenki 1 l in 4 l, soda 60 l in 205 l, kontejner

### Filling:

plastic bottles 1 l & 4 l, barrels 60 l & 205 l, container

## Motorna olja za težka dieselska vozila

### Motor Oils for heavy diesel vehicles

## PETROL Turbo Diesel Ultra 10W-40

SAE 10W-40, ACEA E6-04/2, E7-04/2, E4-99/3, MB 228.5/228.51, MAN M3477, Volvo VDS-3/VDS-3 LSA, MTU Type 3.1, Renault Truck RXD, DAF HP-2...

**PETROL Turbo Diesel Ultra 10W-40** je visoko zmogljivo delno sintetično motorno UHPD olje namenjeno novi generaciji EURO 4 & 5 dieselskih motorjev, ki zahtevajo uporabo olja z nizko vsebnostjo pepela, žvepla in fosforja (Low SAPS). Nizke vsebnosti teh elementov vplivajo na učinkovito delovanje sistemov za čiščenje izpušnih plinov (DPF/CRT) v modernih EURO 4 & 5 motorjih. Primerno je tudi za motorje s SCR tehnologijo. Olje omogoča najdaljše intervale menjave ter zagotavlja vsestransko zaščito EURO 4 & 5 motorja v najtežjih pogojih delovanja.

*PETROL Turbo Diesel Ultra 10W-40 is a partly synthetic Ultra High Performance Diesel engine oil (UHPD) with low sulphated ash, phosphorus and sulphur content (Low SAPS), intended for use in latest EURO 4 & 5 diesel engines. Designed to give good performance on after treatments (DPF/CRT). It is recommended for use in severe duty operations when very long oil drain intervals are required. This oil is also suitable for engines using SCR technology.*

### Tipične lastnosti / Characteristics:

Viskoznost / Kinematic viscosity (100°C; mm <sup>2</sup> /s):	13,5
Plamenišče / Flash point (°C):	238
Točka tečenja / Pour point (°C):	- 33
Gostota / Density (kg/l):	0,860

### Polnjenje:

plastenka 4 l, soda 60 l in 205 l, kontejner

### Filling:

plastic bottles 4l, barrels 60 l & 205, container



## PETROL Turbo Diesel Super 10W-40

SAE 10W-40, ACEA E4-99/3, E5-02, E7-04, A3-98, B3-98/2, B4-98, API CF, MB 228.5/228.3/229.1, MAN M3277/M3275, Volvo VDS-2, Caterpillar, Renault Trucks RXD, DAF, IVECO, Scania LDF, Cummins, MTU Type 3 ...

**PETROL Turbo Diesel Super 10W-40** je delno sintetično motorno UHPD olje, ki presega najnovejše zahteve proizvajalcev težkih dieselskih motorjev. Omogoča najdaljše intervale menjave olja ter zagotavlja vsestransko zaščito motorja v najtežjih pogojih delovanja.

***PETROL Turbo Diesel Super 10W-40** is partly synthetic UHPD motor oil even exceeding the latest requirements of manufacturers in heavy-duty Diesel engines. It provides the longest oil change intervals and universal engine protection in all operating conditions.*

### Tipične lastnosti / Characteristics:

Viskoznost / Kinematic viscosity (100°C; mm <sup>2</sup> /s):	13,5
Plamenišče / Flash point (°C):	228
Točka tečenja / Pour point (°C):	- 39
Gostota / Density (kg/l):	0,867

### Polnjenje:

plastenke 4 l, soda 60 l in 205 l, kontejner

### Filling:

plastic bottles 4 l, barrels 60 l & 205 l, container



## PETROL Turbo Diesel 15W-40

SAE 15W-40, ACEA E7-04, E5-02, B3-98/2, B4-02, A3-02, A2-96/3, API CI-4/SL, Global DHD-1 in 229.1, MB 228.3, MAN M 3275, Volvo VDS-3, Scania LDF (E7), Renault RLD-2, Mack EO-M Plus, Caterpillar ECF-1, Allison C-4, MTU Type 2 ...

**PETROL Turbo Diesel 15W-40** je vrhunsko SHPD motorno olje za najbolj obremenjena težka dieselska vozila. Zagotavlja vsestransko zaščito motorja v vseh pogojih delovanja. Ustreza najnovejšim zahtevam EURO 4 & 5 za motorje s SCR tehnologijo.

***PETROL Turbo Diesel 15W-40** is a top quality, SHPD motor oil for extremely loaded heavy-duty diesel vehicles. It provides universal engine protection in all operating conditions. Designed to give good performance on EURO 4 & 5 after treatments using SCR technology (also EGR without DPF).*

### Tipične lastnosti / Characteristics:

Viskoznost / Kinematic viscosity (100°C; mm <sup>2</sup> /s):	14,5
Plamenišče / Flash point (°C):	220
Točka tečenja / Pour point (°C):	- 30
Gostota / Density (kg/l):	0,889

### Polnjenje:

plastenke 4 l, 10 l in 20 l, soda 60 l in 205 l, kontejner

### Filling:

plastic bottles 4 l, 10 l & 20 l, barrels 60 l & 205 l, container



## PETROL Diesel 15W-40

SAE 15W-40, ACEA E2-96/4, B2-98/2, A2-96/3, API CH-4/SL, MB 228.1/229.1, MAN 271, Volvo VDS, RVI RD, Mack EO-L, Caterpillar TO-2, Allison C-4 ...

**PETROL Diesel 15W-40** je univerzalno motorno olje za težka dieselska vozila. Izpolnjuje tudi zahteve specifikacij za osebna vozila, zato je zelo primerno za mešane vozne parke.

*PETROL Diesel 15W-40 is a universal motor oil recommended for heavy-duty diesel vehicles. It meets the requirements of specifications relating to passenger cars, therefore it is suitable for mixed fleets.*

### Tipične lastnosti / Characteristics:

Viskoznost / Kinematic viscosity (100°C; mm <sup>2</sup> /s):	14,7
Plamenišče / Flash point (°C):	226
Točka tečenja / Pour point (°C):	- 27
Gostota / Density (kg/l):	0,880

### Polnjenje:

plastenke 4 l, 10 l in 20 l, soda 60 l in 205 l, kontejner

### Filling:

plastic bottles 4 l, 10 l & 20 l, barrels 60 l & 205 l, container



## PETROL Diesel 20W-50

SAE 20W-50, ACEA E2-96/4, B2-98/2, A2-96/3, API CG-4/SL, MB 228.1/229.1, MAN 271, RVI RD, Caterpillar TO-2, Allison C-4 ...

**PETROL Diesel 20W-50** je univerzalno motorno olje za težka dieselska vozila, lahko pa se uporablja tudi za osebna vozila. Zaradi višje viskoznosti je še posebej primerno za starejša vozila, kjer se pojavljajo težave s porabo in tlakom olja.

*PETROL Diesel 20W-50 is a universal motor oil recommended for heavy-duty diesel vehicles, but it can also be used for passenger cars. Due to its high viscosity, it is particularly recommended for older vehicles with oil consumption and pressure difficulties.*

### Tipične lastnosti / Characteristics:

Viskoznost / Kinematic viscosity (100°C; mm <sup>2</sup> /s):	18,7
Plamenišče / Flash point (°C):	234
Točka tečenja / Pour point (°C):	- 27
Gostota / Density (kg/l):	0,890

### Polnjenje:

plastenke 4 l, 10 l in 20 l, soda 60 l in 205 l, kontejner

### Filling:

plastic bottles 4 l, 10 l & 20 l, barrels 60 l & 205 l, container



## PETROL Diesel Energy 5W-30

SAE 5W-30, ACEA E4-99/3, API CF, MB 228.5, MAN M3277, Volvo VDS-2, MTU Type 3, Caterpillar, Renault Trucks RxD, DAF HP-1/HP-2, IVECO, Scania, Cummins ...

**PETROL Diesel Energy 5W-30** je popolnoma sintetično fuel economy motorno olje z UHPD lastnostmi, ki celo presegajo najnovejše zahteve proizvajalcev težkih dieselskih motorjev. Olje se odlikuje predvsem po manjši porabi goriva in višjem izkoristku, izredno dolgih intervalih menjave, dobrih detergentnih in disperzantskih lastnostih, zaščiti pred obrabo, korozijo in poliranjem valjev, preprečevanju zgoščevanja olja pri visokih temperaturah ter nizkem penjenju.

***PETROL Diesel Energy 5W-30** is a fully synthetic fuel economy motor oil with UHPD characteristics even exceeding the latest requirements of manufacturers in heavy-duty diesel engines. This oil is primarily distinguished by its lower fuel consumption and higher engine efficiency, extremely long oil change intervals, good detergent and dispersive characteristics, good antiwear, anticorrosion and cylinder polishing protection. It prevents oil from congestion and foaming at high temperatures.*

### Tipične lastnosti / Characteristics:

Viskoznost / Kinematic viscosity (100°C; mm <sup>2</sup> /s):	12,0
Plamenišče / Flash point (°C):	230
Točka tečenja / Pour point (°C):	- 48
Gostota / Density (kg/l):	0,859

### Polnjenje:

plastenka 4 l, soda 60 l in 205 l, kontejner

### Filling:

plastic bottles 4l, barrels 60 l & 205, container

## PETROL Diesel 30

SAE 30, ACEA E2-96/4, API CF/SL, MB 228.0, MAN 270, MTU Type 1 ...

**PETROL Diesel 30** je enogradacijsko motorno olje za težka dieselska vozila. Namenjeno je vsem motorjem in strojem, kjer se zahteva uporaba enogradacijskega olja SAE 30.

***PETROL Diesel 30** is a monograde motor oil for heavy-duty diesel vehicles, designed for all engines and machines where the monograde oil "SAE 30" is required.*

### Tipične lastnosti / Characteristics:

Viskoznost / Kinematic viscosity (100°C; mm <sup>2</sup> /s):	10,8
Plamenišče / Flash point (°C):	230
Točka tečenja / Pour point (°C):	- 27
Gostota / Density (kg/l):	0,880

### Polnjenje:

plastenka 10 l, sod 205 l, kontejner

### Filling:

plastic bottle 10 l, barrel 205 l, container





## PETROL Diesel 40

SAE 40, ACEA E2-96/4, API CF/SL, MB 228.0, MAN 270, MTU TYPE 1 ...

**PETROL Diesel 40** je enogradacijsko motorno olje za težka dieselska vozila. Namenjeno je vsem motorjem in strojem, kjer se zahteva uporaba enogradacijskega olja SAE 40.

***PETROL Diesel 40** is a monograde motor oil for heavy-duty diesel vehicles, designed for all engines and machines where the monograde oil "SAE 40" is required.*

### Tipične lastnosti / Characteristics:

Viskoznost / Kinematic viscosity (100°C; mm <sup>2</sup> /s):	14,5
Plamenišče / Flash point (°C):	236
Točka tečenja / Pour point (°C):	- 24
Gostota / Density (kg/l):	0,890

### Polnjenje:

plastenka 10 l, sod 205 l, kontejner

### Filling:

plastic bottle 10 l, barrel 205 l, container

## ZELENI PROGRAM ZA KMETIJSTVO GREEN PROGRAMME FOR AGRICULTURE

### PETROL Agrotrak TDH Premium

SAE 80W, API GL-4, Volvo VME WB 101 (97303), JI Case MS 1206, 1207, 1209, John Deere JD 20C, Ford New Holland M2C 134 A/B/C/D, M2C 86B/C, GIMA (Massey Ferguson) M1135, M1141, M1143 (homologacija M1143-1/M/062), M1145 (homologacija M1145-1/P/019), Detroit Diesel Allison C-3, Caterpillar TO-2, ZF TE-ML03E, 05F, 06K

**PETROL Agrotrak TDH Premium** je vrhunsko univerzalno traktorsko transmisijsko olje (UTTO), namenjeno uporabi v traktorjih in delovnih strojih, kjer se menjalnik, transmisija, zadnji most, mokre zavore in hidravlika mažejo z enim oljem. Agrotrak THD Premium ima izrazito uravnotežene torne lastnosti katere omogočajo visoko učinkovitost mokrih zavor in PTO sklopov. Lahko se uporablja tudi namensko v menjalnikih in hidravliki drugih vozil in delovnih strojih, za katere je predpisana kakovost olja API GL-4 in viskoznost SAE 80W.

***PETROL Agrotrak TDH Premium** is advanced universal tractor transmission oil (UTTO), designed for tractors and heavy machinery where the same oil is used for lubricating the transmission gear, transmission, rear axle, wet brakes and hydraulic system. Agrotrak THD Premium has specifically balanced frictional properties for maximum effectiveness of both wet brakes and PTO clutches. It is also suitable for use in transmission gears and hydraulic systems of other vehicles requiring an API GL-4 quality and SAE 80W viscosity.*

### Tipične lastnosti / Characteristics:

Viskoznost / Kinematic viscosity (40°C; mm <sup>2</sup> /s):	58,0
Plamenišče / Flash point (°C):	224
Točka tečenja / Pour point (°C):	- 45
Gostota / Density (kg/l):	0,884

### Polnjenje:

plastenka 10 l in sod 205 l

### Filling:

plastic bottle 10 l and barrel 205 l

Motorna olja PETROL izdeluje CHEVRONTEXACO Global Lubricants.



**PETROL**

[www.petrol.si](http://www.petrol.si)

## PETROL Biolub 46

### ISO VG 46, VDMA 24 568 - HETG

**PETROL Biolub 46** je biološko razgradljivo hidravlično olje, izdelano na osnovi oljne repice. Olje je posebej primerno za vsa tista področja uporabe, kjer obstaja možnost onesnaženja zemlje ali vode z mazivom (traktorska hidravlika, poljedelski, gozdarski, gradbeni stroji, vodne zapornice...).

***PETROL Biolub 46** is a biologically degradable hydraulic oil produced from rape seed oil. It is particularly recommended for all areas of application where soil or water may be polluted with lubricants (tractors hydraulic systems, farm machinery, heavy machinery, canal locks...).*

#### Tipične lastnosti / Characteristics:

Viskoznost / Kinematic viscosity (100°C; mm <sup>2</sup> /s):	46
Plamenišče / Flash point (°C):	200
Točka tečenja / Pour point (°C):	- 36
Gostota / Density (kg/l):	0,923

#### Polnjenje:

plastenka 10 l in sod 205 l

#### Filling:

plastic bottle 10 l and barrel 205 l



## PETROL Verigol BIO Plus

### SIST 1017

**PETROL Verigol Bio Plus** je vrhunsko biološko razgradljivo olje za verige gozdarskih žag. Odlikujejo ga dobra biološka razgradljivost, odlična mazalnost, oprijemljivost in lepljivost ter korozijska zaščita.

***PETROL Verigol Plus** is a top quality, biologically degradable oil designed for lubricating power saw chains. It provides good biological degradability, excellent lubricating capacity, adhesiveness and corrosion resistance.*

#### Tipične lastnosti / Characteristics:

Viskoznost / Kinematic viscosity (100°C; mm <sup>2</sup> /s):	81,7
Plamenišče / Flash point (°C):	200,5
Točka tečenja / Pour point (°C):	- 36
Gostota / Density (kg/l):	0,923

#### Polnjenje:

plastenki 1 l in 4 l ter sod 205 l

#### Filling:

plastic bottles 1 l & 4 l and barrel 205 l



## PETROL Tratol

SAE 30, Briggs&Stratton, Tecumseh, API SL / CF, ACEA E2-96/4, MB 228.0, MAN 270, MTU Type 1

**PETROL Tratol** je kakovostno motorno olje za mazanje 4-taktnih vrtnih kosilnic. Lahko ga uporabljamo tudi za manjše motokultivatorje, traktorje in ostalo vrtno mehanizacijo, saj je prilagojeno specifičnim lastnostim njihovega delovanja (visoka temperatura, prah, umazanija, velike obremenitve...).

***PETROL Tratol** is quality motor oil specially designed for lubricating four-stroke lawn mower engines. Other applications include: rotary cultivators, tractors and other garden machinery. Due to its special properties, it is suitable for use in all conditions (dust, dirt...).*

### Tipične lastnosti / Characteristics:

Viskoznost / Kinematic viscosity (100°C; mm <sup>2</sup> /s):	10,9
Plamenišče / Flash point (°C):	228
Točka tečenja / Pour point (°C):	- 27
Gostota / Density (kg/l):	0,888

### Polnjenje:

plastenka 1 l

### Filling:

plastic bottle 1 l



## OLJA ZA MENJALNIKE IN DIFERENCIALE OILS FOR TRANSMISSIONS AND DIFFERENTIALS

### PETROL GL Multi 75W-90

SAE 75W-90, API GL-4, API GL-5, API MT-1, ZF TE-ML 02B, 05B, 07A, 08, 12B, 16F, 17B, MAN 3343SL, Scania STO 1:0

**PETROL GL Multi 75W-90** je popolnoma sintetično večgradacijsko olje, namenjeno mazanju vseh vrst zobniških prenosnikov, kjer se priporočajo olja specifikacije API GL-4 (ročni menjalniki, reduktorji ...) in specifikacije API GL-5 (diferenciali, planetna gonila ...).

***PETROL GL Multi 75W-90** is a fully synthetic multigrade oil designed for lubricating in all sorts of gear compounds where oils meeting API GL-4 (manual transmissions, reducing gears ...) and API GL-5 (differentials, planetary drives ...) are recommended.*

#### Tipične lastnosti / Characteristics:

Viskoznost / Kinematic viscosity (100°C; mm <sup>2</sup> /s):	98
Plamenišče / Flash point (°C):	202
Točka tečenja / Pour point (°C):	- 54
Gostota / Density (kg/l):	0,868

#### Polnjenje:

soda 60 l in 205 l ter kontejner

#### Filling:

barrels 60 l & 205 l and container

### PETROL GL 5 80W-90

SAE 80W-90, API GL-5, MIL-L-2105 C/D, NATO Code 0-226, ...

**PETROL GL-5 80W-90** je mineralno večgradacijsko hipoidno olje z izredno širokim temperaturnim območjem delovanja, namenjeno mazanju menjalnikov, diferencialov in ostalih zobniških prenosov, kjer se zahteva olje vrste API GL-5.

***PETROL GL-5 80W-90** is a premium quality mineral based hypoid oil with exceptional wide temperature performance designed for use in transmission gearboxes, differentials and gear compounds where an oil meeting API GL-5 is required.*

#### Tipične lastnosti / Characteristics:

Viskoznost / Kinematic viscosity (100°C; mm <sup>2</sup> /s):	135
Plamenišče / Flash point (°C):	212
Točka tečenja / Pour point (°C):	- 33
Gostota / Density (kg/l):	0,899

#### Polnjenje:

soda 60 l in 205 l

#### Filling:

barrels 60 l & 205 l



## PETROL GL 5 85W-90

SAE 85W-90, API GL-5, MB 235.0, ZF TE-ML 05A, 07A, 12A, 16C, 17B, MAN 342, MIL-L-2105D ...

**PETROL GL-5 85W-90** je večgradacijsko hipoidno olje, namenjeno mazanju menjalnikov, diferencialov in ostalih zobniških prenosov, kjer se zahteva olje vrste API GL-5.

***PETROL GL-5 85W-90** is a multigrade hypoid oil designed for use in transmissions gearboxes, differentials and gear compounds where an oil meeting API GL-5 is required.*

### Tipične lastnosti / Characteristics:

Viskoznost / Kinematic viscosity (100°C; mm <sup>2</sup> /s):	175
Plamenišče / Flash point (°C):	220
Točka tečenja / Pour point (°C):	- 33
Gostota / Density (kg/l):	0,900

### Polnjenje:

plastenki 1 l in 4 l, soda 60 l in 205 l ter kontejner

### Filling:

plastic bottles 1 l & 4 l, barrels 60 l & 205 l and container

## PETROL GL 5 85W-140

SAE 85W-140, API GL-5, MIL-L- 2105D, ZF TE-ML 05A, 07A, 12A, 16A, 17B ...

**PETROL GL-5 85W-140** je večgradacijsko hipoidno olje, namenjeno mazanju izjemno obremenjenih menjalnikov, diferencialov in ostalih zobniških prenosov, kjer se zahteva olje vrste API GL-5.

***PETROL GL-5 85W-140** is a multigrade hypoid oil designed for use in extremely loaded transmissions gearboxes, differentials and gear compounds where an oil meeting API GL-5 is required.*

### Tipične lastnosti / Characteristics:

Viskoznost / Kinematic viscosity (100°C; mm <sup>2</sup> /s):	360
Plamenišče / Flash point (°C):	214
Točka tečenja / Pour point (°C):	- 18
Gostota / Density (kg/l):	0,907

### Polnjenje:

plastenki 1 l in 4 l ter soda 60 l in 205 l ter kontejner

### Filling:

plastic bottles 1 l & 4 l and barrels 60 l & 205 l and container



## PETROL GL 4 80W

SAE 80W, API GL-4, MB 235.1, ZF TE-ML 02A, 08, 16A, 17A, MAN 341, MIL-L-2105A ...

**PETROL GL-4 80W** je mineralno transmisijsko olje, namenjeno mazanju menjalnikov in ostalih zobniških prenosov, kjer se zahteva olje vrste API GL-4.

***PETROL GL-4 80W** is a mineral transmission oil designed for use in transmissions gearboxes and gear compounds where an oil meeting API GL-4 is required.*

### Tipične lastnosti / Characteristics:

Viskoznost / Kinematic viscosity (100°C; mm <sup>2</sup> /s):	82
Plamenišče / Flash point (°C):	220
Točka tečenja / Pour point (°C):	- 36
Gostota / Density (kg/l):	0,889

### Polnjenje:

plastenki 1 l in 4 l, soda 60 l in 205 l ter kontejner

### Filling:

plastic bottles 1 l & 4 l, barrels 60 l & 205 l and container

## PETROL ATF Matic DX III

General Motors Dexron III G-GM6417 M (Dexron III F, II E), MAN 339F, Ford M2C -138 CD, M2C 166H, Mercon M-940127, Allison C-4, Voith 55.6335.10 (Diwa and Midimat), ZF TE-ML-02F, 04D, 17C, ZF Lenksysteme TE-ML 09A, 09B, Caterpillar TO- 2, Demison HF-0 ...

**PETROL ATF Matic DX III** je visokokakovostno olje za avtomatske menjalnike osebnih in tovornih vozil. Primerno je tudi za hidravlične (servo) volane in ostale hidravlične sisteme s črpalkami Vickers, Sunstrand in Denison (HF 0).

***PETROL ATF Matic DX III** is a high quality oil for automatic transmissions in passenger cars and trucks. It is also suitable for hydraulic power steering and other hydraulic systems with Vickers, Sunstrand and Denison (HF 0) pumps.*

### Tipične lastnosti / Characteristics:

Viskoznost / Kinematic viscosity (100°C; mm <sup>2</sup> /s):	33.8
Plamenišče / Flash point (°C):	200
Točka tečenja / Pour point (°C):	- 51
Gostota / Density (kg/l):	0,899

### Polnjenje:

plastenki 1 l in 4 l, soda 60 l in 205 l ter kontejner

### Filling:

plastic bottles 1 l & 4 l, barrels 60 l & 205 l and container



## MOTORNA OLJA ZA DVOTAKTNE MOTORJE IN SKUTERJE MOTOR OILS FOR TWO-STROKE PETROL ENGINES & SKUTERS

### PETROL 2-T MIX

ISO L-EGD, JASO FC, TISI, API TC

**PETROL 2-T MIX** je univerzalno olje za pripravo mešanice za dvotaktne bencinske motorje. Primerno je za mazanje dvotaktnih motorjev pri motornih kolesih in mopedih, malih kmetijskih strojih in vrtnih kosilnicah, malih izvenkrmnih motorjih in podobnih strojih.

*PETROL 2-T MIX is a universal oil suitable for the preparation of a gasoline blend used in two-stroke petrol engines. It is recommended for the lubrication of two-stroke engines in motorcycles and motor scooters, light farm machinery, lawn mowers, small outboard engines and similar devices.*

#### Tipične lastnosti / Characteristics:

Viskoznost / Kinematic viscosity (100°C; mm <sup>2</sup> /s):	8,3
Plamenišče / Flash point (°C):	100
Točka tečenja / Pour point (°C):	- 18
Gostota / Density (kg/l):	0,868

#### Polnjenje:

plastenki 0,5 l in 1 l

#### Filling:

plastic bottles 0,5 l and 1 l

### PETROL 2-T SINT

ISO L-EGD, JASO FC/FD, API TC, TISI, Husqvarna 242 chainsaw, Rotax snow mobile

**PETROL 2-T SINT** je visoko zmogljivo, popolnoma sintetično motorno olje za pripravo mešanice za dvotaktne bencinske motorje. Zagotavlja odlično mazanje najbolj obremenjenih dvotaktnih motorjev pri modernih motornih kolesih, mopedih, malih kmetijskih strojih, motornih žagah, vrtnih kosilnicah, kosah in podobnih strojih.

*PETROL 2-T SINT is a heavy-duty, race proven synthetic motor oil suitable for the preparation of a blend used in two-stroke petrol engines. It provides excellent lubrication of extremely loaded two-stroke engines in all modern types of motorcycles, motor scooters, light farm machinery, power saws, lawn mowers, scythes and similar devices.*

#### Tipične lastnosti / Characteristics:

Viskoznost / Kinematic viscosity (100°C; mm <sup>2</sup> /s):	8,1
Plamenišče / Flash point (°C):	100
Točka tečenja / Pour point (°C):	- 20
Gostota / Density (kg/l):	0,868

#### Polnjenje:

plastenki 0,5 l in 1 l

#### Filling:

plastic bottles 0,5 l and 1 l



## PETROL 2-T SCOOTER

ISO L-EGD, JASO FC/FD, TISI

**PETROL 2-T SCOOTER** je specialno visokokakovostno olje za dvotaktne (2-T) motorje skuterjev.

**PETROL 2-T SCOOTER** is a special high quality motor oil for two-stroke (2-T) Scooter motor engines.

### Tipične lastnosti / Characteristics:

Viskoznost / Kinematic viscosity (100°C; mm <sup>2</sup> /s):	8,5
Plamenišče / Flash point (°C):	85
Točka tečenja / Pour point (°C):	- 40
Gostota / Density (kg/l):	0,887

### Polnjenje:

plastenki 0,5 l in 1 l

### Filling:

plastic bottles 0,5 l and 1 l



## PETROL 4-T SCOOTER

ACEA A3-02, API SL, JASO MA

**PETROL 4-T SCOOTER 10W-40** je specialno visokokakovostno delno sintetično olje za štiriktaktne (4-T) motorje skuterjev.

**PETROL 4-T SCOOTER 10W-40** is a special high quality partly synthetic motor oil for four-stroke (4-T) Scooter motor engines.

### Tipične lastnosti / Characteristics:

Viskoznost / Kinematic viscosity (100°C; mm <sup>2</sup> /s):	14,7
Plamenišče / Flash point (°C):	228
Točka tečenja / Pour point (°C):	- 28
Gostota / Density (kg/l):	0,873

### Polnjenje:

plastenka 1 l

### Filling:

plastic bottle 1 l





## HLADILNE TEKOČINE - ANTIFRIZI COOLING - ANTI-FREEZE FLUIDS

### Antifriz K

**MB 325.3, Audi/VW/Škoda/Seat TL 774D (G12), MAN 324 SNF, Renault ...**

**Antifriz K** je koncentrirano sredstvo za zaščito vseh vrst hladilnih sistemov in motorjev pred zmrzovanjem in korozijo. Ščiti najmanj 5 let. Antifriz K nalijemo v hladilni sistem vozila in v priporočenem razmerju razredčimo z vodo.

*Antifriz K is a highly concentrated product that protects all types of cooling systems and prevents freezing and corrosion of engine. Provides protection for at least 5 years. It needs to be poured into the cooling system of the automobile and dilute with water as recommended.*

#### Polnjenje:

plastenke 1 l, 4 l in 22 kg, sod 60 kg, sod 220 kg ter kontejner 1000 kg

#### Filling:

plastic bottles 1 l, 4 l & 22 kg, barrel 60 kg, barrel 220 kg and container 1000 kg



### Antifriz - 40°C

**MB 326.3, Audi/VW/Škoda/Seat TL 774D (G12), MAN 324 SNF, Renault ...**

**Antifriz - 40°C** je razredčeno sredstvo za zaščito vseh vrst hladilnih sistemov in motorjev pred korozijo in zmrzovanjem do - 40°C. Ščiti najmanj 5 let. Nalijemo ga v hladilni sistem vozila. Dodatno redčenje ni potrebno.

*Antifriz - 40°C diluted product for the protection of all cooling systems and the prevention of freezing and corrosion of the engine to - 40°C. Provides protection for at least 5 years. It needs to be poured into the cooling system of the automobile and not diluted with water.*

#### Polnjenje:

plastenki 1 l in 4 l ter sod 220 kg

#### Filling:

plastic bottles 1 l & 4 l and barrel 220 kg



## ZAVORNA TEKOČINA BRAKE FLUIDS

### PETROL Brake fluid DOT-4

FMVSS116 DOT4, DOT3, SAE J 1703, SAE J 1704

**PETROL Brake Fluid DOT-4** je zavorna tekočina, ki jo lahko uporabljamo v vseh vrstah hidravličnih zavornih sistemov in hidravličnih sklopov, ki zahtevajo uporabo zavorne tekočine DOT-3 ali DOT 4. Izdelana je na osnovi glikolnih etrov in dodatkov za izboljšanje mazalnih lastnosti ter dodatkov proti koroziji in oksidaciji.

***PETROL Brake Fluid DOT-4** is a brake fluid for all hydraulic brake and clutch systems which complies with specification DOT-3 or DOT-4. Brake Fluid DOT-4 has been formulated from glycol ethers. It contains effective lubricants, corrosion inhibitors and antioxidants.*

#### Tipične lastnosti / Characteristics:

Viskoznost / Kinematic viscosity (100°C; mm <sup>2</sup> /s):	min 1,5
Plamenišče / Flash point (°C):	260
Točka tečenja / Wet flash point (°C):	min 165
Gostota / Density (kg/l):	0,899

#### Polnjenje:

pločevinka 0,5 l

#### Filling:

can 0.5 l

## DODATKI ADDITIVES

### DIESEL Plus

**DIESEL Plus** je večnamenski dodatek za dieselsko gorivo. Čisti ključne sestavne dele sistema za dovod goriva ter jih hkrati ščiti pred nastajanjem oblog in usedlin. Znižuje porabo goriva, zvišuje cetansko število, preprečuje penjenje goriva in ščiti pred nastankom korozije. Je okolju prijazen, saj zmanjšuje emisijo izpušnih plinov v okolje. Primeren je za vse vrste dieselskih motorjev.

***DIESEL Plus** is a multi-purpose additive for Diesel engines. It cleans the key component parts of the fuel supply system, simultaneously protecting the system from deposits and sediments. It provides lower consumption of fuel, cetane number boost and anti-corrosion protection; it prevents fuel from foaming. DIESEL Plus is environment-friendly as it reduces the emission of exhaust gases. It is suitable for all types of Diesel engines.*

#### Polnjenje:

plastenka 0.25 l

#### Filling:

plastic bottle 0.25 l



## BENCIN Plus

**BENCIN Plus** je večnamenski dodatek za motorne bencine. Čisti sestavne dele motorja (ventile, uplinjač, vbrizgalni sistem in zgorevalni prostor) ter jih hkrati ščiti pred nastajanjem oblog in usedlin. Znižuje porabo goriva in emisijo izpušnih plinov. Primeren je za vse vrste bencinskih motorjev s katalizatorjem in/ali turbo polnilnikom oziroma brez.

***BENCIN Plus** is a highly effective multi-purpose additive for petrol engines, produced in accordance with the latest technology. It cleans the component parts of the engine (valves, carburettor, injection system and combustion chamber), simultaneously protecting these parts from deposits and sediments. It provides lower consumption of fuel and lower emission of exhaust gases. It is suitable for all types of petrol engines either with or without a catalytic converter and/or turbo charger.*

**Polnjenje:**

plastenka 0.25 l

**Filling:**

plastic bottle 0.25 l



## DIESEL Winter Protect

**DIESEL Winter Protect** je nizko temperaturni dodatek za dieselsko gorivo. Preprečuje izločanje kristalov parafina in njihovo usedanje na dno avtomobilskega rezervoarja ter s tem težave, ki se pojavljajo pri nizkih zunanjih temperaturah (mašenje filtrov, črpalk in cevovodov). Uporabnost goriva izboljša tudi do temperature  $-25^{\circ}\text{C}$ . Dodatek učinkuje preventivno, zato ga moramo gorivu dodati, ko je še bistro, njegova temperatura pa nad  $0^{\circ}\text{C}$ . Primeren je za vse vrste dieselskih motorjev.

***DIESEL Winter Protect** is a highly efficient additive for Diesel fuel suitable for use at low temperature conditions. It prevents the crystals of paraffin from segregating and depositing at the bottom of car tanks, eliminating thus the difficulties appearing when outside temperatures are low (plugging of filters, pumps and pipes). It improves fuel properties at temperatures as low as  $-25^{\circ}\text{C}$ . The additive acts preventively, therefore it should be added to fuel before any difficulties arise. It is recommended to be added when fuel is still clear and its temperature is above  $0^{\circ}\text{C}$ . It is suitable for all types of Diesel engines.*

**Polnjenje:**

plastenka 0.25 l

**Filling:**

plastic bottle 0.25 l



Na voljo je tudi v koncentrirani obliki **Diesel Winter Protect K**, kjer 1 l zadošča za 1000 l goriva.

**Polnjenje:**

plastenka 0.25l in pločevinka 1 l

Available also in a concentrated version **Diesel Winter Protect K**, where recommended dosage is 1 l of additive for 1000 l of fuel.

**Filling:**

plastic bottle 0.25 l and metal bottle 1 l



## VENTIL Plus

**VENTIL Plus** je nadomestek svinca v neosvinčenih bencinih. Zagotavlja popolno zaščito mehkih ventilskih sedežev. Primeren je za vse vrste bencinskih motorjev brez katalizatorja in vse vrste neosvinčenih bencinov.

*VENTIL Plus provides complete protection of soft valve seats when unleaded gasoline is used. It is suitable for all types of petrol engines without a catalytic converter and for all types of unleaded gasoline.*

**Polnjenje:**

plastenka 0.25 l

**Filling:**

plastic bottle 0.25 l



## SEALANT Plus

V hladilnih sistemih vozil sčasoma pride do razpok, ki so posledica korozije, vibracij, udarcev in drugih vzrokov. **SEALANT Plus** je sredstvo, s katerim lahko nastale razpoke učinkovito in hitro zatesnimo ter s tem preprečimo izgubo hladilne tekočine, zaradi katere pride do pregrevanja, izgube moči, pogosto pa tudi do resnejših okvar motorja. Lahko ga uporabljamo ne glede na vrsto in tip hladilne tekočine (antifriz). Ne škoduje tesnilnim in drugim materialom v hladilnem sistemu.

*SEALANT Plus is an additive used for sealing cracks that appear in the cooling systems of vehicles as a result of corrosion, vibrations and similar. This additive provides fast and efficient sealing of cracks, preventing thus the loss of coolant, which might induce overheating, loss of power and consequently serious engine damages. It is suitable for use with all types of coolants (anti-freeze). It does not harm sealants and other materials in the cooling system.*

**Polnjenje:**

plastenka 0.25 l

**Filling:**

plastic bottle 0.25 l



## PETROL AdBlue

### AUS 32-DIN 70 070

**PETROL AdBlue** je nestrupena 32,5% raztopina sečnine (urea) v vodi, ki se uporablja za kemično zmanjševanje dušikovih oksidov pri Euro 4 in Euro 5 dieselskih motorjih opremljenimi s SCR katalizatorji.

*PETROL AdBlue is a non-toxic high-purity 32,5% aqueous urea solution for the secondary treatment of exhaust gases in Euro 4 and Euro 5 heavy duty diesel engines equipped with SCR systems.*

**Polnjenje:**

plastenka 10 l

**Filling:**

plastic bottle 10 l



## SREDSTVA ZA NEGO CARE PRODUCTS

### Vitrex - 38°C

**Vitrex - 38°C** je tekočina za čiščenje vetrobranskih stekel in njihovo zaščito pred zmrzovanjem. Učinkuje večkratno: ščiti pred zmrzovanjem, preprečuje zaledenitev vodnih šob, čisti steklo in odstranjuje insekte. Odišavljeno. Ni strupeno. Razredčimo ga z vodo v priporočenem razmerju.

***Vitrex - 38 °C** is an anti-freeze fluid cleanser that cleans and protects the windshield. Multipurpose: protects glass from cold and freezing, prevents freezing of windshield water dispensers, cleans glass and removes accumulated dirt and insects. Non-toxic fluid with fresh scent. Dilute it with water as recommended.*

#### Polnjenje:

plastenki 1 l in 4 l ter sod 50 l

#### Filling:

plastic bottles 1 l & 4 l and barrel 50 l

### Letni Vitrex

**Letni Vitrex** je koncentrirano čistilo, ki se doda vodi za čiščenje vetrobranskega stekla. Odstranjuje ostanke insektov, olja in drugih nečistoč, ki ovirajo pogled skozi vetrobransko steklo in s tem varno vožnjo. Odišavljeno. Ni strupeno. Brez fosfatov. Vsebina plastenke zadošča za pripravo 5 litrov čistilne raztopine. Ustrezno količino izdelka nalijemo v rezervoar in dopolnimo z vodo.

***Summer Vitrex** is a concentrated windshield cleaner to which water must be added. It removes insects, oil and other dirt and impurities that prevent clear vision through the windshield and inhibit safe driving. Non-toxic fluid. Pleasant aroma. No phosphates. The contents of the plastic bottle are sufficient for the preparation of 5 litres of cleaning fluid. Pour the appropriate quantity of product into the reservoir and fill with water.*

#### Polnjenje:

plastenki 1 l in 4 l ter sod 50 l

#### Filling:

plastic bottles 1 l & 4 l and barrel 50 l

### Vitrex - koncentrat

**Vitrex - koncentrat** je močno koncentrirano čistilo, ki se doda vodi za čiščenje vetrobranskih stekel. Odstranjuje vse vrste umazanije, s tem pa zagotavlja jasen pogled skozi vetrobransko steklo. Vsebina plastenke zadošča za pripravo 31 litrov čistilne raztopine, kar zagotavlja 10-kratno polnjenje običajnega avtomobilskega rezervoarja za čistilno tekočino.

***Vitrex - concentrate** for highly concentrated windshield cleanser to which water must be added. Removes all types of dirt and impurities and ensures clear vision through the windshield. The contents of the plastic bottle are sufficient for 31 litres of cleaning fluid, enough for 10 refills of the standard size automobile reservoir for cleaning fluid.*

#### Polnjenje:

plastenka 250 ml

#### Filling:

plastic bottle 250 ml



**PETROL**

[www.petrol.si](http://www.petrol.si)

## **Avtošampon z učinkom odbijanja kapljic** **Autoshampoo with water drop repellent**

**Šampon** kakovostno zaščiti lakirano površino vozila in tako zagotovi, da se nečistoče z nje dobro odbijajo. Ker hkrati zagotavlja, da kapljice spolzijo s površine vozila, je potreba po sušenju avtomobilskih površin minimalna.

*This quality **shampoo** protects the painted surface of the automobile and repels soil and other impurities from the surface. Because the shampoo also contains an agent that causes water drops to slide off the surface, the need to dry after shampooing is minimal.*

**Polnjenje:**  
plastenka 1 l

**Filling:**  
plastic bottle 1 l



## **Avtošampon z dodatno zaščito z voskom** **Autoshampoo with wax protection**

**Šampon** kakovostno zaščiti lakirano površino vozila. S tako zaščitene površine se nečistoče dobro odbijajo, vosek pa še dodatno neguje vozilo.

*This quality **shampoo** protects the painted surface of the automobile. The cleaned surface repels soil and other impurities and the wax provides added protection.*

**Polnjenje:**  
plastenka 1 l in sod 50 l

**Filling:**  
plastic bottle 1 l and barrel 50 l



## **PETROL Odmrzovalec stekel in Odmrzovalec ključavnic** **PETROL glass de-icer, PETROL lock de-icer**

**PETROL Odmrzovalec stekel, PETROL Odmrzovalec ključavnic** v sekundi odtali zamrznjena stekla in ključavnice. Preprečuje ponovno zamrznitev. Skrbi za čisti pogled.

***PETROL glass de-icer, PETROL lock de-icer** melts frost on glass surfaces and locks instantly. It prevents further freezing and helps to keep the windshield clear.*

**Polnjenje:**  
plastenka 500 ml

**Filling:**  
plastic can 500 ml



## PETROL Cockpit spray VANILIJA

### PETROL Cockpit spray VANILLA

**PETROL Cockpit spray VANILIJA** je sredstvo za nego armaturne plošče, prinaša čudovit vonj vanilje. Čisti in neguje vse plastične, in gumijaste dele v avtomobilu. Deluje antistatično, odbija prah in neguje tudi armature iz lesa. Osveži barvo, varuje plastiko pred lomljivostjo in ji daje visok sijaj.

***PETROL Cockpit spray VANILLA** cleans, polishes and preserves dashboards, leaving a pleasant vanilla aroma. Freshens and restores interior plastics, rubber and wood and leaves an anti-static dust repellent finish. Brightens the colours, prevents fragility of plastic and leaves a glossy coating that protects plastic surfaces.*

#### Polnjenje:

pločevinka 400 ml

#### Filling:

can 400 ml



## PETROL Motor spray

**PETROL Motor spray** čisti hitro, temeljito in odstranjuje olje, mast in ostale nečistoče z avtomobilskega motorja. Uporablja se lahko tudi za čiščenje agregatov, karoserije in orodij.

***PETROL Motor spray 400 ml** cleans quickly and radically, and removes oils, greases, grime, dirt and other contaminants from car engine. Also suitable for cleaning the generators, car bodies and tools.*

#### Polnjenje:

pločevinka 400 ml

#### Filling:

can 400 ml



## Destilirana voda

### Distilled water

**Destilirana voda** za akumulatorje, avtomobilske hladilnike in likalnike.

***Distilled water** for batteries, radiators and irons.*

#### Polnjenje:

plastenka 1 l, 5 l

#### Filling:

plastic bottle 1 l, 5 l



**PETROL**

Petrol, Slovenska energetska družba, d.d., Ljubljana  
Dunajska c. 50, 1527 Ljubljana  
tel.: 01 47 14 234  
[www.petrol.si](http://www.petrol.si)  
[info@petrol.si](mailto:info@petrol.si)

